

REMARKS

Entry of this Preliminary Amendment is respectfully requested prior to the first Office Action and prior to the calculation of the filing fee for the subject application. After entry of this Amendment, claims 1 - 3 are pending in the application. Claims 1 and 2 have been amended.

The Abstract has been placed on a separate page. The Abstract is the same as on the International Patent Application except that reference numbers have been deleted, and the word "having" has replaced the word "comprising."

A handwritten, corrected copy of the specification is enclosed showing the changes which have been made to the specification as required by Section 608.01(Q) and 714.20(1) of the Manual of Patent Examining Procedure. The Substitute Specification filed herewith has been amended to utilize idiomatic English, correct minor typographical and grammatical errors and to conform the application to current United States Patent practice. The Substitute Specification includes no new subject matter; but does include the same changes handwritten in red in the attached, corrected, original specification. The Substitute Specification also includes the Abstract on a separate sheet as noted in this Amendment.

It is submitted that this Amendment has antecedent basis in the application as originally filed, including the specification, claims and drawings, and that this Amendment does not add any new subject matter to the application. Consideration of the application as amended is requested. It is submitted that this Amendment places the application in suitable condition for allowance; notice of which is requested.

If the Examiner feels that prosecution of the present application can be expedited by way of an Examiner's Amendment, the Examiner is invited to contact the Applicant's attorney at the telephone number listed below.

Respectfully submitted,

YOUNG & BASILE, P.C.


Darlene P. Condra

Attorney for Applicant(s)
Registration No. 37113
(248) 649-3333

3001 West Big Beaver Rd., Suite 624
Troy, Michigan 48084-3107
Dated: April 21, 2005
DPC/dge

10/521497

Method for coating, in particular for painting, objects

=====

BACKGROUND OF THE INVENTION (later + updated)

The invention relates to a method for coating, in
5 particular for painting, objects, especially vehicle
bodies, comprising a plurality of parts which are initially
separate and can subsequently be connected to one another,
in which method the objects are guided on skids with the
aid of a conveying system through at least one coating
10 booth, in which at least one application device is
arranged.

In the known, currently employed methods of this type which
are used for painting vehicle bodies, the vehicle bodies
15 are coated in the fully assembled state. The movable parts
releasably attached to the vehicle body, for example doors,
front gate and rear gate, have to be pivoted with the aid
of robots during the painting operation in order to be able
to reach all the surfaces to be painted. With increasing
20 throughput through the painting installation, the
proportion of non-value-added processes, such as the moving
of the robots in and out, the opening of flaps and doors,
and the moving to coating positions, also increases. The
efficiency of the robots thus decreases, so that above a
25 certain throughput an additional coating line is required.

SUMMARY OF THE INVENTION (later + updated)

The object of the present invention is to specify a method
of the type mentioned at the outset, in which the
efficiency of the coating operation is increased.

30

This object is achieved according to the invention in that
at least one part of the objects is guided through the
coating booth on its own skid separately from the other
parts.

According to the invention, all the apparatus for moving the movable parts, in the case of vehicle bodies for opening the flaps and doors, can be dispensed with, thereby
5 reducing the non-value-added operations. At the same time, the coating process, which until now has taken place on a stop-and-go operating basis in automated coating installations, can be carried out on a continuously
operating basis again, despite the use of coating robots
10 which guide the application devices. This also cuts down on non-value-added processes. The number of robots overall can be reduced; the booths can be designed shorter and narrower. The markedly reduced booth area leads to corresponding savings in the conditioning of the booth air.
15 Owing to the continuous operation, the robots guiding the application device do not need to have a translatory axis parallel to the movement direction of the objects.

The various parts belonging to the same object do not
20 necessarily have to pass through the coating process at the same time or immediately after one another.

In an advantageous embodiment of the method according to the invention, the skid on which the at least one part is
25 carried follows the skid or skids which carries or carry the other parts of the object, through the same coating booth. They are thus coated by the same application device from the same source of the coating material, ensuring identical coatings and thus in particular also colour
30 equality.

Alternatively, the at least one part of the object can also be guided on its own skid through a different coating booth

to the other parts of the object, the application devices in both coating booths being fed from a common paint supply means. This too allows the desired identity of the coating, in particular colour equality, to be achieved.

5

BRIEF DESCRIPTION OF THE DRAWING (enter+underline)

An exemplary embodiment of the invention is explained in more detail below with reference to the drawing; the single figure shows a highly schematic plan view of a coating booth with two skids situated therein.

10

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT (enter+underline)

The coating booth is denoted by the reference symbol 1 in the figure; it is traversed in the direction of the arrow 3 by skids 2, 2' carrying parts 5, 6, 7, 8 to be coated. The skid-conveying system required for this, and also the doors on the narrow sides of the coating booth 1 which are required to allow the loaded skids 2, 2' to pass through, are omitted from the figure for reasons of clarity.

Situated inside the coating booth 1 on opposite sides of the movement path of the objects 5, 6, 7, 8 to be coated are application devices 9, 10 which are fed from a common supply source and by which the parts 5, 6, 7, 8 guided past on the skids 2, 2' are coated. The application devices 9, 10 are guided by robots which need to have solely movement axes in the vertical and horizontal direction perpendicular to the movement direction, but not a movement axis parallel to the movement direction.

In the present case, the parts 5, 6, 7, 8 to be coated are the roof 5, the front gate 6, the rear gate 7 and the doors 8 of a vehicle body. The roof 5, front gate 6 and rear gate 7 are arranged on the first skid 2 in such a way that they do not touch one another and all the surfaces to

be coated can be reached by the application devices 9, 10 without moving these parts 5, 6, 7. The doors 8 are mounted on the second skid 2', which follows the first skid 2 in the movement direction (arrow 3). The doors 8 are arranged
5 on the second skid 2' likewise in such a way that all their surfaces to be coated can be reached by the application devices 9, 10 without having to be moved.

After both skids 2, 2' have passed through, all the
10 parts 5, 6, 7, 8 of the vehicle body will have been coated without the aid of a robot to move the parts 5, 6, 7, 8. They can now be assembled to form a ready-coated vehicle body or supplied to separate preassembly lines:

15 The skids 2, 2' can be conventionally constructed. They each have in particular two runners 13, 14, 13', 14' which run parallel to the movement direction and are connected to one another by two cross-struts in the case illustrated. On the supporting structure 11, 11' thus formed there are
20 mounted holders (not illustrated specifically) for the parts 5, 6, 7, which are rigidly constructed, i.e. do not need to allow pivoting or other movement of the parts 5, 6, 7, 8.

Patent Claims

=====

1. Method for coating, in particular for painting,
5 objects, especially vehicle bodies, comprising a plurality of parts which are initially separate and can subsequently be connected to one another, in which method the objects are guided on skids with the aid of a conveying system through at least one coating
10 station, in which at least one application device is arranged,

characterised in that

15 at least one part (8) of the objects is guided through the coating booth (8) on its own skid (2') separately from the other parts (5, 6, 7).
2. Method according to claim 1, characterised in that the
20 skid (2') on which the at least one part (8) is carried follows the skid or skids (2) which carries or carry the other parts (5, 6, 7) of the objects, through the same coating booth (8).
- 25 3. Method according to claim 1, characterised in that the at least one part of the object is led on its own skid through a different coating booth to the other parts of the object, the application devices in both coating booths being fed from a common paint supply means.